1901
B1

BAKER

Theory and Practice of Bicycle Race-Track Construction

Civil Engineering
B. S.

1901

UNIVERSITY
OF
ILL. LIBRARY

Learning and Labor.
LIBRARY
OF THE
University of Illinois.
CLASS. BOOK. VOLUME.
1901 B1
Accession No.

The person charging this material is responsible for its return to the library from which it was withdrawn on or before the **Latest Date** stamped below.

Theft, mutilation, and underlining of books are reasons for disciplinary action and may result in dismissal from the University.

UNIVERSITY OF ILLINOIS LIBRARY AT URBANA-CHAMPAIGN

BUILDING USE ONLY

RETURN TO THESES COLLECTION

MAR 10 1979

MAR 10 1979

JAN 24 1981

BUILDING USE ONLY

JAN 24 1981

L161—O-1096

UNIVERSITY OF ILLINOIS

May 29, 1901. 190

THIS IS TO CERTIFY THAT THE THESIS PREPARED UNDER MY SUPERVISION BY

Horatio Weber Baker

ENTITLED Theory and Practice of Bicycle Race-Track Construction

IS APPROVED BY ME AS FULFILLING THIS PART OF THE REQUIREMENTS FOR THE DEGREE

OF Bachelor of Science in Civil Engineering

Ira O. Baker.

HEAD OF DEPARTMENT OF Civil Engineering

3

51800

1901
B1

BICYCLE RACE-TRACKS

With the extended use of bicycles has come a relatively small class of people who choose bicycle racing as a recreation or even a profession. From these riders has come a demand for tracks built espicially for bicycle racing. It is the purpose of this thesis to enquire into the theory and practice of bicycle race-track construction.

The design of a track may be considered under three heads: first, the ground plan; second, the banking or superelevation of the outer edge; and third, the material to be used in the construction.

I. GROUND PLAN

The following principles must be borne in mind in the design for the ground plan of a bicycle race-track.

1. The length and form of the track will depend upon the size and shape of the area

UIUC

available.

2. Large tracks are expensive to construct, and and do not afford the spectators a good view of the racers. Very small tracks are objectionable because of the sharp curvature and consequent high banking.

3. For convience it is desirable that the length of the track shall be an aliquot part of a mile. The length of all bicycle tracks is measured on a line eighteen inches from the inner edge of the track, called the pole line.

4. The field should not be so wide that the spectators are unable to see easily all parts of the race.

6. The curves should be of such form that the rider experiences no lurch due to change of direction in following the curve.

7. On curves a superelevation of the outer edge is required. Since the superelevation can not be effected instantly, a varying curvature must be used to permit the joining of the flat tangents with the fully banked curves.

The conditions which best meet

Digitized by the Internet Archive
in 2013

http://archive.org/details/theorypracticeo0bake

the first four requirements can be determined only by experience while the conditions meeting the remainder may be determined by mathematical analysis. It is proposed to describe the more noted tracks with a view of determining the present status of the best practice, and then to design a track which shall fully meet all of the requirements.

Present Practice

The first tracks were very crudely laid out. For example, it is stated that the curves of one of the earliest tracks in the country, the one half mile track at Hampden Park, Springfield, Mass. were located by running a bicycle over the ground and staking out the path.

Most of the early tracks were semi-circles connected by tangents. Among these are the ones at Waltham, Mass., and Louisville, Ky. Each is one third of a mile in length with semi-circles of 150 feet radius and tangents 109 feet long. The tracks have each held many world's records

and were for a time very fashionable.

In 1896 Mr. C. E. Stanley, then consulting engineer of the Pope Manufacturing Co. designed and constructed the famous Manhattan Beach track. This seems to have been the first attempt to meet scientifically requirements 6 and 7 stated above. This track is one third of a mile in length and consists of two tangents connected by "elliptical curves" to circular ones (see Fig. 1 p. 5). Apparently the elliptical curve, AB, consists of a series of nine circular arcs, each 5° long, having radii ranging in length from 210 to 174 feet. The circular arc, BC, is 38°17' long and has a radius of 136 feet. The tangents are 313.4 feet long, the elliptical curves 162.4 feet long, and the circular arcs 90.9 feet. The track is 26.5 feet wide save the home stretch which is 40 feet — the widest track in the country.

In 1897 a quarter mile track was constructed at Racine, Wis. of exactly the same ground plan as the Manhattan-



ONE THIRD MILE TRACK
AT
MANHATTAN BEACH
LONG ISLAND NEW YORK

FIG. 1.

track except that the tangents were shortened.

The Charles River track Boston Mass is one third of a mile in length, the circular curves being joined to the tangents by easement curves consisting of inverted circular arcs. This track is a later design by the designer of the Waltham track and may be considered as forming in the mind of the designer a test of the importance of joining the tangents and curves by arcs of varying radius.

In 1916 the well known track in Sheffield Park Chicago was constructed according to the design and under the direction of Mr F C Schneider, the Engineer of the West Park Board. The track is one half mile in length with tangents 316.5 feet long connecting semi-circular ends having radius of 300.32 feet (see Fig. 3 p. 7). The track is 25 feet in width save the home stretch which is 35 feet. The widening of the home stretch was accomplished by moving the center for the arc AB

FIELD PARK
CHICAGO ILLINOIS

FIG. 2.

to feet toward the home stretch.

These examples represent the most advanced theory of the [illegible] of bicycle race tracks. Others almost all others have been built by exhibitors or professional riders without reference to the principles involved.

Correct Form

The length and form of the track will depend upon the size and shape of the area available. However these factors will vary so greatly that they can not be considered in a general design; and hence it will be assumed that the area available is unlimited.

Length. Mr. Hawley probably the best authority on bicycle tracks in this country, states in a private communication, that in his opinion the ideal track should be four laps to the mile. In view of this statement and of the reduced cost over a larger track, the design will be made for a track one fourth of a mile in length.

Proportions of Field. To determine the relation between the length and breadth of the field of these track which may be considered as the best representatives of current practice, Table I was compiled. The term called "Hawley" is the ideal form suggested by Mr. Hawley in the communication above referred to.

TABLE I

PROPORTIONS OF FIELD

REPRESENTATIVE OF BEST CURRENT PRACTICE

Arranged in order of Roundness

Ref. No.	Name of Track	Length of Field	Width of Field	Ratio	Length of Track	Width of Field	Ratio
1	Garfield Park	976.5	600	0.614	2640	600	0.227
2	Racine	499.6	295	0.590	1320	295	0.223
3	Hawley	519.6	275	0.529	1320	275	0.209
4	Waltham	709.0	300	0.423	1760	300	0.170
5	Manhattan	715.5	295	0.410	1760	295	0.168
			Mean	0.513		Mean	0.199

From a study of the table we may conclude that a track to meet the requirements of current practice should have a field about twice as long as wide, or width of field about one fifth of the length of the track. A field of these proportions will

give a track affording the spectators a good view of all parts of the race.

Form of Curves. In fig. 3 the black line represents a portion of the path of a track consisting of semi-circles connected by tangents. A racer riding in the direction indicated, when passing at B the



Fig 3.

point of tangency, will not be able to change instantly from a straight path with an infinite radius to a curved path with a uniform finite radius; but will involuntarily take a curvilinear curve having a uniformly decreasing radius. Similarly in entering a tangent from a curve, the rider will swing out from

the first line of the tangent to a curve of increasing radius. The red line of Fig. 3 shows the path approximately taken by the rider. Since all distances are measured in the horizontal, and since all excess distance rides adds to the time of the race, there is a decided advantage in having the first bit of the same curvature as that of the path naturally taken by the rider. The greater ease with which a wheel can be guided around a curve of gradually varying radius also adds to the speed of the race.

For reasons which will be discussed later, the surface of the track in curves should be elevated at the outer edge. This superelevation varies inversely as the radius of curvature. Since it is impossible to change instantly from flat tangents to banked curves, a track consisting of semicircles and tangents will not permit the proper superelevation of the outer edge. If, however, the tangent is connected to the circular arc by a curve of gradually varying curvature, the banking in-

crosses gradually from one to the tangent to the full amount of the superelevation of the circular arc.

The Transition Spiral* devised by Prof. A. N. Talbot is a curve of uniformly increasing radius which has been much used on railroads in recent years as an easement curve, and seems particularly adapted to bicycle race-tracks. According to Professor Talbot's definition, "The transition spiral is a curve whose superelevation increases directly as the distance along the curve from the point of tangency." Without entering into a discussion of the mathematical relations of the curve, the writer will endeavor to apply the principles of the spiral to the design of the proposed plans for a quarter-mile bicycle race-track.

---

* For an elaborate treatment of the curve see "The Transition Spiral" by Arthur N. Talbot in Technograph No. 5 (p. 71; reprint of same with additions, in Technograph No. 13 p. 19. Also published separately by the author 4 × 6½" paper, pp. 64.

The following notation will be used, being that given by Professor Talbot.

P.S. = point of spiral, i.e., the point of tangency of the spiral and the tangent.

P.C.C. = point where the spiral compounds with the circular curve.

R = radius of curvature of the spiral at any point.

D = degree-of-curve of the spiral at any point; called D, at the P.C.C.

a = rate of change of the degree-of-curve of the spiral per 100-ft. station. It is the degree-of-curve of the spiral at 100 feet from the P.S.

L = number of 100-ft. stations from the P.S. along the curve to any point on the spiral; called L, for the whole spiral.

Δ = angle between the initial tangent and the tangent the spiral at any point; called Δ, for the whole curve.

Θ = deflection angle at the P.S., from the initial tangent to any point on the spiral; called Θ, for the whole spiral.

X = abscissa of any point on the above referred to the "P.S. as the origin, and to the initial tangent as the axis of X.

Y = ordinate of the same point measured at right angles to the above axis.

Having decided that the trial should consist of circular arcs connected to tangent by transition spirals, it is necessary to determine the dimensions of the circular arcs. Each one of the pavements of the trial roads is considered as symmetrical. The total length of a pavement will be 330 feet in length. In Fig. 4 this pavement is represented by



Fig. 4

ABCH of which AB is a tangent, BC the

transition spiral, and C.H. a circular arc. In order to give sufficient tangent when about to start curves, the length of the tangent AB will be taken at 30 feet. In reality there will be about twice this amount of practically straight track, since the change of direction of the first 25 feet of the spiral will be less than one half - degree.

The problem now is to determine the value of Δ_1 and the radius of the circular arc. The length of the combined curves being known, an expression for this length will be deduced in terms of the unknown quantities.

The length of the circular arc is $\frac{I}{D}$, I being the intersection angle COH, and D the degree-of-curve of the arc. From similar triangles, the angle GFC = the angle EOC; and since GFC is Δ_1, $I = 90° - \Delta_1$. Also D of the circular arc = D_1 of the transition spiral, and hence the length of the circular arc is

$$\frac{90° - \Delta_1}{D_1} \quad \text{---------- (1)}$$

The length of the transition spiral

is obtained from the formula $\Delta_1 = \frac{1}{2} D_1 l$, and is equal to

$$\frac{2\Delta_1}{D} \qquad (2)$$

Adding (1) and (2) and equating the sum to the curve length of the natural curves, expressed in 100-ft stations, we have:

$$\frac{10 + \Delta_1}{D_1} = 3.0 \qquad (3)$$

Equation (3) having two unknown quantities is indeterminate, and hence of the quantities must be assumed. The circular curves of the Newcastle track with a radius of 136 feet have proved themselves fairly satisfactory. Curves with much shorter radii could not be used, because of the high banking required; and in order to be on the safe side a radius of 140 feet will be used for the circular curves. Since $D_1 = \frac{5729.65}{R}$, therefore if $R = 140$ feet, $D_1 = 40°926$. Using this value of D_1 in equation (3) gives $\Delta_1 = 32°778'' = 32° 46.7'$. Then knowing Δ_1 and D_1, the spiral becomes determinate.

The chord may be located on the field on either of two ways; namely, by the deflection angles from the initial tangent, and the chords measured along the curve; or by offsets from the tangent to the curve.

The most desired line is that of the field line — the line to which distances are measured — but this line is not marked in the field. In consideration of construction, the inside edge of the track is the line that is staked out; and it is necessary to use this line 11 inches from the field line. The radius of the curve must be 11 inches less than that of the field line, and hence D, will be a little larger; but the deflection angle for the inside edge of the track will have the same Δ, as that for the field line. In Tables II and III, page 18, the data are given for laying out the chord by the two methods mentioned above.

Fig. 5, page 19, shows the complete design. The track is 25 feet wide except the Long stretch, which is 35 feet. Since the form of the outside

TABLE II

CHORDS AND DEFLECTION ANGLES FOR LOCATING THE SPIRAL FOR THE INSIDE EDGE OF THE TRACK

Point on Spiral	Distance from the P.S. along the curve	Deflection Angle at the P.S. from the Initial Tangent
P.S.	0.0 Feet	0° 00'
1	25.0	0° 16'.3
2	50.0	1° 05'.2
3	75.0	2° 27'.0
4	100.0	4° 21'.0
5	120.0	6° 15'.6
6	140.0	8° 30'.7
P.C.C.	158.47	10° 53'.7

TABLE III

RECTANGULAR COORDINATES FOR LOCATING THE SPIRAL FOR THE INSIDE EDGE OF THE TRACK

Point on Spiral	Distance from the P.S. on the Tangent Prolonged	Offset Perpendicular to the Tangent
P.S	0.00 Feet	0.00 Feet
1	25.00	0.12
2	49.98	0.95
3	74.88	3.20
4	99.48	7.57
5	118.71	13.03
6	137.18	20.55
P.C.C.	153 20	29.53



DESIGN FOR A

FIG. 5.

edge of the track is not important & may be located by measuring from the stake set on the inside edge.

The field is 11 5/6 in wide or long. It is a little easier around than the rest of the tracks previously cited. But if the field were much narrower the curvature would be sharper, curves with a large radius are of more importance than a narrower field.

The above design meets all the requirements stated on pages 1 and 2; and possess some important features over an irregular race-track construction.

2. BANKING

According to the principles of mechanics the force required to deflect a body from a rectilinear path is:

$$\frac{Mv^2}{\rho} \text{ or } \frac{Wv^2}{g\rho}$$

in which

M = mass of the body,
V = velocity in feet per second,
ρ = radius of curvature
W = weight of the body
g = acceleration due to gravity, in feet per second = 32.16.

This force acts radially in the plane of the curve; and since the path of a body on a bicycle track is a curve whose plane is horizontal, this force acts horizontally.

The rider is acted upon by two forces — gravity and centrifugal force. These forces and their resultant are shown in Fig. 6, p. 22.

If the resultant is normal to the surface of the track, practically no slant

of the rider will be required to balance the wheel and hence he may give his attention chiefly to steering. The resultant



Fig. 6.

will be normal to the surface of the track, if the surface makes the same angle with the horizontal that the resultant makes with the vertical. From Fig. 6, we see that

$$\tan\theta = \frac{V^2}{\rho g} \qquad \text{(1)}$$

This formula gives the relation between the angle of inclination, the velocity, and the radius of curvature.

During the design of the ground plan the radius of curvature will be known; but since the banking depends upon the velocity, the track must be designed for some particular speed. In deciding upon the velocity to be adopted, it is necessary to

determine whether the maximum velocity should be increased. If the track is to be used chiefly for races it should be designed for the maximum velocity desired to be reached; but if the racing is occasional the curves should be designed for the average velocity. To determine the facts in this respect, the banking of the most noted tracks will be investigated.

In the early track high banking seems to have been avoided for two reasons: first because of a baseless prejudice against it, and second, because many of the races written in competition were so slow as not to require high banking.

The curves of the Louisville and Gotham tracks have a banking such that at a speed of a mile in 2 minutes and 53 seconds the wheel is normal to the surface. The superelevation of the Manhattan track was computed for a speed of a mile in 2 minutes and 32 seconds. Fig. 1 page 5, shows the banking of this track, expressed in angles with the horizontal. The curves of the

Racine track, which has the same radii as the Hamilton track is banked for a speed of a mile in 1 minutes and 16 seconds — a little higher speed than for the Hamilton track.

The banking of the Indianapolis track was computed for a speed of a mile in 2 minutes. The angles of the superelevation of this track are shown in Fig 2 page 7. It is stated that persons on this track, making a mile in 1 (1/16) of a mile in 1 minute and 41 seconds, leaned slightly toward the inside of the track. Since the banking was figured for a 2 minute pair, the rider going at a speed of 1 minute and 41 seconds would be compelled to lean toward the center of the track to balance the centrifugal force. This shows in a crude way the agreement of theory and practice.

Many short wooden tracks have been constructed with very high banking. A table among these is a track of a mile track laid in Springfield, Mass., in July 190.. The curves (apparently semi-circular) are banked for a speed of a mile in 1 minute

in 1 26 seconds. The inclination of the angle on the curves being 48° and on the tangents 30° — the steepest track known. The track is pronounced by racing men to be the fastest track in the world.

A summary of the speeds for which the various tracks were constructed is shown in Table IV.

TABLE IV
SPEED FOR WHICH THE BANKING WAS CONSTRUCTED

Name of Track	SPEED	
	Feet per Second	Time for one mile
Waltham & Louisville	30.53	2 min. 53 sec.
Manhattan	34.24	2 " 34 "
Racine, Wis.	36.17	2 " 26 "
Garfield Park	44.00	2 " 00 "
Springfield Mass.	66.00	1 " 20 "

It is obvious that the choice of the velocity to be used depends upon experience and judgement, and not upon mathematical relations. If the track is to be used for motor racing without competition, the velocity should be high, perhaps 66 feet per second, or a mile in 1 minute and 20 seconds; but if the track is to be used for races of

competition without motor pacing, the velocity should be about 44 feet per second, or a mile in 2 minutes.

The values shown for the curves in design, Fig. 5, page 19, are computed for a velocity of 44 feet per second or a mile in 1 minute and 50 seconds. Should the speed vary materially from this value, the wheel will not stand exactly normal to the surface and there will be a tendency to slip. The tire of a wheel will not slip unless the angle between the plane of the wheel and the normal to the track is greater than the angle of repose. Experiments by the writer gave a value for the angle of repose of a bicycle upon a cement sidewalk of 23° 15' and practically the same value for a smooth wooden surface. Therefore there will be no danger of the wheel's slipping, if the speed be increased until the wheel leans 23° inside of the normal to the track, or if the speed be decreased until the wheel inclines 23° outside of the normal. For the track in Fig. 5, page 19,

the position of the wheel corresponds to a speed of a mile in 1 minute and 15 seconds, and the second to a mile in 1 minute and 53 seconds. The former is the speed of the fastest steam-motor cars, and the latter is slower than any suburban loop is run. Therefore, the superelevation of the track shown in Fig. 5 is adjusted for a speed of 45 feet per second or a mile in 1 minute and 50 seconds. It can be used for considerably faster cars and should be safe for slow cars and counter riding. However it will not be possible to attain the highest speed unless the superelevation is adjusted approximately to that speed, since otherwise part of the rider's attention and effort is required to balance his weight.

It is the practice of some designers to compute the banking for one speed and then construct the track with an arbitrary fractional part of the computed value. For example, the banking of the Manhattan track was nominally computed on a 2 minute unit, and then restricted

with a corresponding speed [illegible] of
[illegible] [illegible] [illegible]
a mile upward in 2 minutes and 31
seconds [illegible].

Mr Langley recently received from
G Tate Bird & Sons patents, which
has given considerable attention to the
design of bicycle-pedal tracks, suggesting
that the surface of the tracks be curved
in manner as shown in Fig. 7.



Fig. 7

Such a surface Mr Langley claims, would make it easier for one rider to pass another, since to accomplish this he must ride at a higher speed but less would require a steeper inclination. This conclusion is wrong, since the speed of the increased radius almost exactly counteracts the effect of the increased velocity, requiring therefore the same angle of

inclination. Mr. Hawley has shown that the concave surface would prevent a rider from flying off the track should a momentary loss of control occur. This advantage is not important, as the banking of most tracks enables a momentary loss of control without accident. The tendency to "lay the track" may be checked by painting parallel yellow lines on the surface of the track. This feature was used on the Manhattan Track and is described in detail on page 33. However the concave surface would be objectionable for a track having rapid banking. A third objection to the concave surface is that it would be very expensive to construct. There is nothing to prevent the use of this surface.

3. MATERIALS OF CONSTRUCTION

The surface of a bicycle race-track may be loam, clay, cinders, wood or cement.

Most of the early tracks were constructed of either loam or clay. Such surfaces are cheap and easy to construct. On the other hand, the cost of maintenance of an earth surface is great, and high banking can not be used, and moisture destroys temporarily the usefulness of the track. A certain Paris track was constructed of clay covered with a thin layer of fine chalk dust. This track at one time was very popular — but chiefly on account of its excellent surface.

A surface of cinders is cheap and easy to construct, and is not affected by moisture. However, cinders can not be used with high banking, and such a surface is expensive to maintain and wounds received by a rider in falling often prove serious.

A well constructed wooden sur-

face is very fast, and for reason has been used in many short tracks, in which high banking is required. An example of such construction is the Coliseum track at Springfield, Mass. The surface consists of strips, one inch square, nailed to a foundation of 2" x 12" timbers for indoor use where a track must be constructed temporarily, wooden construction has decided advantages. For outdoor use wooden tracks are uneconomical because of the destructive action of the elements.

In most of the larger tracks today constructed, cement surfaces have been used. Such a surface is practically indestructible, since there is no expense for maintenance. Its usefulness is not destroyed by moisture and any degree of smoothness may be obtained. Cement was used in the construction of the Waltham track, the Newcastle, the Manhattan, the Garden track, and the Ravine tracks. The surface of the Manhattan is most fast,

ideal and [illegible] shown in Fig. 8, the embankment is composed of four distinct layers: first,



Fig. 8.

a gravel embankment; second, a 8-inch layer of ash concrete; third, a 3-inch layer of crushed granite concrete; and fourth, a top layer of 1½ inches of cement mortar. The gravel was deposited in thin layers and thoroughly compacted by rolling. The purpose of the ash concrete is to confine the gravel embankment against [illegible] and consists of Portland cement and ashes in the ratio of 1 to 10. The 3-inch layer of granite consists of Portland cement, 1 part sand and 7 parts of crushed granite. The top layer consists of 1½

inches of mortar composed of 1 part Portland cement 1 part sand, and 3 parts broken granite. Lamp black was mixed with the mortar to prevent the glare of the sun. The surface of the mortar was roughened by placing bits of broken stone sticking in the ties. Spaces were also taken out to embed the stones between the blocks of concrete which are of sufficient weight to withstand the action of the waves. The surface of the Macadam track has withstood the test of a three years trial, as well as the watering of several years and has proved itself very satisfactory.

A novel feature of this track is the four parallel lead wires, one inch wide, counter to the surface of the track. A person riding a bicycle with his head bent down on the handle bars does not notice that it is approaching the wires, and if it does not guide its wheel accurately it will run off the track. The guide lines were laid as the floor was

the curves and thus prevent such an accident.

While the determination of the surface to be used is a matter of judgement, the writer believes that a cement surface such as the Manhattan track will give the best conditions for racing and durability.

UNIVERSITY OF ILLINOIS-URBANA
3 0112 086762082